

Product datasheet

Specifications



EVS400F TM315D circuit breaker - 3P/3d

EVS400F3315

Main

Range of product	EasyPact EVS
Product or component type	Circuit breaker
Device short name	EVS400F
Circuit breaker application	Distribution
Poles description	3P
Protected poles description	3d
Suitability for isolation	Yes

Complementary

Neutral position	Left
[In] rated current	315 A at 40 °C
Breaking capacity code	F
Network type	AC
Network frequency	50/60 Hz
Control type	Toggle
Mounting mode	Fixed
Mounting support	Backplate
Upside connection	Front
Downside connection	Front
[Ui] rated insulation voltage	690 V conforming to EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-2
[Ue] rated operational voltage	440 V AC 50/60 Hz conforming to EN/IEC 60947-2 400 V AC 50/60 Hz conforming to GB 14048.2
Breaking capacity	40 kA Icu at 220/240 V AC 50/60 Hz conforming to EN/IEC 60947-2 36 kA Icu at 380/400 V AC 50/60 Hz conforming to EN/IEC 60947-2 36 kA Icu at 415 V AC 50/60 Hz conforming to EN/IEC 60947-2 30 kA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 40 kA Icu at 220/230 V AC 50/60 Hz conforming to GB 14048.2 35 kA Icu at 380/400 V AC 50/60 Hz conforming to GB 14048.2
Utilisation category	Category A
[Ics] rated service breaking capacity	40 kA at 220/230 V AC 50/60 Hz conforming to GB 14048.2 35 kA at 380/400 V AC 50/60 Hz conforming to GB 14048.2 40 kA at 200/240 V AC 50/60 Hz conforming to EN/IEC 60947-2 36 kA at 380/400 V AC 50/60 Hz conforming to EN/IEC 60947-2

36 kA at 415 V AC 50/60 Hz conforming to EN/IEC 60947-2
23 kA at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2

Mechanical durability	15000 cycles conforming to EN/IEC 60947-2 10000 cycles conforming to GB 14048.2
Electrical durability	12000 cycles 415 V In/2 conforming to EN/IEC 60947-2 8000 cycles 400 V In conforming to GB 14048.2
Connection pitch	45 mm
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit rating	315 A at 40 °C
Protection type	Overload protection (thermal) Short-circuit protection (magnetic)
Long time pick-up adjustment type Ir	Fixed
Long time pick-up adjustment range	1 In
Long time delay adjustment type	Fixed
Instantaneous pick-up adjustment type li	Fixed
Integral instant protection	3200 kA
Height	255 mm
Width	140 mm
Depth	110 mm
Net weight	6.05 kg

Environment

Standards	EN 60947-2 IEC 60947-2
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	4.873 kg
Package 1 Height	15.6 cm
Package 1 width	29 cm
Package 1 Length	15.8 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	3
Package 2 Weight	16.08 kg
Package 2 Height	24.1 cm
Package 2 width	37.8 cm

Package 2 Length	49.8 cm
Unit Type of Package 3	PAL
Number of Units in Package 3	48
Package 3 Weight	257.4 kg
Package 3 Height	90 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information